

ESTEEM™ GB315

315 Litre Gas Boosted Hills Solar Hot Water System



Hills Solar Hot Water Systems

Climate change due to greenhouse emissions presents an immediate and growing threat to our fragile planet. The sun provides a limitless source of free non-polluting energy every day. A Hills Solar Evacuated Tube Hot Water System can efficiently capture this free energy and provide you with up to 80% savings on your hot water heating costs. Considering Australia is one of the sunniest countries on the planet it makes sense to utilise this resource by installing a Hills Esteem™ Solar Evacuated Tube Hot Water System. Not only will you save money but you will also reduce your family's CO₂ emissions by up to 3 tonnes per year.

Hills Evacuated Tubes have passed the AS/NZS 2712:2007 Standard Freeze Test to -15° C.

Hills Evacuated Tubes have passed the AS/NZS 2712:2007 Standard testing for hail resistance.

Hills Evacuated Tubes are manufactured from high quality Borosilicate Glass and have a 10-year warranty.

Gas Boosting


Hills Solar offers a choice of gas boosting using Bosch continuous highflow gas booster, 21e or 26e on all GB315 Systems to ensure a continual flow of hot water on low thermal days. When water below 60° C is drawn from the tank, the gas booster will boost the water temperature to 60° C ensuring that only the water drawn is heated; therefore, saving energy.

Evacuated Solar Tubes

Evacuated tube technology delivers significantly better performance than traditional absorbers on the market today. Their advanced design incorporates tubes that consist of 2 layers of borosilicate glass with a vacuum layer between them. The vacuum acts like a thermos flask, retaining up to 97% of the thermal energy, resulting in an increased efficiency.

The Sun's solar energy is then transferred to the manifold via the heat pipe located in each tube. The small amount of evaporative liquid in each tube is super heated by the Sun's solar energy and forms into a vapour. The vapour rises to the top of each pipe. Heat transfer then occurs between the pipe and water passing through the manifold. The water is then transferred to the tank.

The cylindrical design of the tubes ensures effective collection of the Sun's solar energy throughout the entire day.



Hills Solar Consumer Advice Line

1300 363 386

Bosch Gas Booster		
Bosch product	Bosch 21e	Bosch 26e
Bosch part number	YS217ORA	YS267ORA
Installation	External	External
Ignition	Electronic	Electronic
L/min (25°C rise)	21	26
Number of bathrooms	2	2-3
Minimum operating inlet water pressure (kPa)	100	100
Mj/H	170	200
Star rating	5.56	5.53
Minimum flow (L/min)	2.5	2.5
Minimum constant water pressure for maximum flow (kPa)	130	230
Antifrost	Standard	Standard
Gas type	NG/LPG	NG/LPG
Electrical supply	230VAC-240V 50Hz 10amp weatherproof power point required within 500mm of the unit	
Unit height (mm)	520	600
Unit width (mm)	350	350
Unit depth (mm)	170	170
Carton weight (kg)	19	22
Natural gas pipe connection	20mm 3/4"	20mm 3/4"
LP gas pipe connection	20mm 3/4"	20mm 3/4"
Cold water pipe connection	20mm 3/4"	20mm 3/4"
Hot water pipe connection	20mm 3/4"	20mm 3/4"
Power consumption	240VAC/36W in standby, 125W when anti freeze mode is on	

315 Litre Tank	
Size in Litres (Actual)	315 (327)
Height	1980mm
Diameter	580mm
Weight Empty	63kg
Weight Full	390kg
Hot Water Outlet	1495mm
Return Flow to Tank	465mm
Cold Water Inlet	365mm
Electric Cable Entry	255mm



Warranty*	Parts	Labour
Tank	10 years	1 year
EST Collectors	10 years	1 year
Gas Booster Heat Exchanger	10 years	3 years
Gas Booster - Other Parts*	3 years	3 years
Electrical Components	1 year	1 year
Pump	1 year	1 year
Mounting Frame	10 years	1 year

*Conditions Apply. For full details visit www.hillsolar.com.au or view the warranty card.

Suggested Tank Size	
160 Litre#	~ Electric / Gas Boosted ~ 1 to 2 People
250 Litre#	~ Electric / Gas Boosted ~ 3 to 4 People
315 Litre#	~ Electric / Gas Boosted ~ 5 to 6 People

*Suggested usage only.

System Information

Product Description	22 Tube Collector	30 Tube Collector	30 Tube Collector	40 Tube Collector
Product Code - LPG	GB-315-21LP-22	GB-315-21LP-30	GB-315-25LP-30##	GB-315-25LP-40##
Product Code - NG	GB-315-21NG-22	GB-315-21NG-30	GB-315-25NG-30##	GB-315-25NG-40##
Weight - Standard Frame, Manifold & Tubes	82kg	108kg	108kg	148kg
Height of Collector (including Manifold)	2000mm	2000mm	2000mm	2000mm
Width of Collector	1845mm	2485mm	2485mm	3470mm**
Distance between Inlet and Outlet Ports	1775mm	2415mm	2415mm	3400mm**
Surface area of Collector	3.69m ²	4.97m ²	4.97m ²	6.74m ²
Absorber area of Collector	1.76m ²	2.40m ²	2.40m ²	3.2m ²
Aperture area of Collector	2.086m ²	2.844m ²	2.844m ²	3.792m ²
Water that Manifold in Collector holds	1260ml	1770ml	1770ml	2330ml
Weight of Low Pitched Roof Frame	10.5kg	11.1kg	11.1kg	17.1kg
Weight of A-Frame	11.5kg	12.1kg	12.1kg	19.6kg
No. of REC's for an installation per zone	22 Tube Collector	30 Tube Collector	30 Tube Collector	40 Tube Collector
Zone 1 - 315L 21e and 26e Gas Boosted	30	37	37	43
Zone 2 - 315L 21e and 26e Gas Boosted	32	39	39	44
Zone 3 - 315L 21e and 26e Gas Boosted	30	37	37	43
Zone 4 - 315L 21e and 26e Gas Boosted	26	32	32	38

** May vary depending on installation. ## All orders 25LP or 25NG will receive 26e as standard.